



THE ELEVATOR MAXIMIZED

ES-8 AVALANCHE ELEVATOR

ES-8 AVALANCHE



Operator's platform



Self-propelled feature



Easy access serviceability



COE ORCHARD EQUIPMENT INC.
3453 Riviera Road Live Oak, CA 95953
Ph (530) 695-5121 Fax (530) 695-5128
WWW.COESHAKERS.COM

SPECIFICATIONS & FEATURES

- John Deere 4045 74HP Tier 4 final engine
- High debris radiator
- ECOOL variable electric cooling system
- Oil & Fuel coolers
- Dual dry element air cleaner w/ pre-cleaner
- Low side trailer height capability with 90 degree top section
- 48 inch wide belts with planetary reduction drive & piston motor belt drive system
- 48" wide hopper conveyor with front & side unloading
- Soft start belts
- *DUALFORCE* Hydrostatic driven belts & ground drive system
- INCONTROL interface with belt & blower adjustments
- Single joystick control
- POWERMAX operating system
- Top section blower
- Flanged V section frame construction
- LED lights package
- Leaf spring suspension with air bags
- Heavy duty axle
- Heavy duty tires
- Heavy duty modular construction
- Towing brake lights
- Tow wire harness & storage compartment
- Powder coated finish

The COE ES-8 Avalanche elevator was designed specifically for high capacity non-stop unloading of pistachios. Compatible with side & front loading bank outs. The hydrostatically driven 48" wide belts quickly carry away product and reduces bank out unloading time to keep harvester up time maximized. The standard self-propelled feature allows for quick placement without needing a tow vehicle at the loading site.