



**FLORY  
SUPER V  
V62 SERIES SWEEPER**

PO BOX 908  
4737 TOOMES RD  
SALIDA CA 95368  
[www.goflory.com](http://www.goflory.com)

209-545-1167



# SUPER V V62 SERIES SWEEPER



## SPECIFICATIONS

|                          |  |
|--------------------------|--|
| <b>ENGINE</b>            | CAT, 4.4 LITER TURBO, TIER 4F                                  |
| <b>HORSEPOWER</b>        | 142 HP   |
| <b>FUEL TYPE</b>         | DIESEL #2, ULTRA LOW SULFUR                                    |
| <b>FUEL CAPACITY</b>     | 70 GAL.  |
| <b>DEF CAPACITY</b>      | 8 GAL.   |
| <b>HYD. OIL CAPACITY</b> | 55 GAL.  |
| <b>GROUND SPEED</b>      | LOW RANGE: 0 - 8 MPH<br>HIGH RANGE: 0 - 15 MPH                 |
| <b>TIRES</b>             | FRONT: 31 X 13.50 - 15, 8 PLY<br>REAR: 31 X 15.50 - 15, 10 PLY |
| <b>WEIGHT</b>            | 13,200 LBS. (WITH 4 FT. - 5 IN. HEADS)                         |

## FEATURES

- The Flory Super V maximizes the speed and efficiency of harvest by reducing the number of sweeping passes, machines and operators required
- In-cab push-button adjustment of blower speed, spout and brush position
- One-touch button automatically lowers sweeper heads, which hydraulically float to follow the terrain
- Next generation air-cab with 1/2" shatter resistant windows to improve safety and comfort
- Trunnion mount rear axle provides a flexible chassis for traction across rough and uneven terrain
- Proven sturdy 5 bar head and "Align-Mount" reel for extended bearing and reel life
- Fail-Safe parking brake system that automatically engages when the engine is off
- Now includes dust containment curtain for sweeper heads (not shown)
- Turn signals and flashers for improved road safety
- Rear view camera

## OPTIONS

- Head Size (See Table)
- Blower Spout Type (Shown with Berm Spouts)
- 4 Wheel Drive • Heater • Sprayer Kit (Hyd. Valve with Rear Couplers)



**HEADS AND BLOWERS FOLD**  
FOR EASE OF TRANSPORTATION



## SWEEPING WIDTHS

| MODEL | HEAD SIZE              | RECOMMENDED TREE ROW SPACING (FT.) |    |    |    |    |
|-------|------------------------|------------------------------------|----|----|----|----|
|       |                        | 20                                 | 21 | 22 | 23 | 24 |
| 44V62 | DUAL 4.5 FT. + BRUSHES |                                    |    |    |    |    |
| 55V62 | DUAL 5.5 FT. + BRUSHES |                                    |    |    |    |    |
| 66V62 | DUAL 6.5 FT. + BRUSHES |                                    |    |    |    |    |

NOTE: MAY VARY DEPENDING ON CONDITIONS

